

cito Plus 136-ACNA-N37A-FN

cito Plus 1000 W, 13.56 MHz

Product specification

Type Designation	cito Plus 136-ACNA-N37A-FN
Part Number	64001121
Frequency (MHz)	13.56 MHz
RF Power (W)	600 W
AC Input	230 VAC
Max. delivered power into mismatch (W)	120 W
Load impedance (Ohms)	50
RF Connector (Ohms)	N-type
RF power regulation mode	P forward, P delivered or Process feedback
Regulation (%)	± 1 % of setpoint or ± 0.1 % of full rated power
RF on rise time (ms)	< 20 ms
RF off fall time (ms)	< 1 ms
Pulse Mode	No
Pulse rise time (μ s)	< 1 μ s
Pulse fall time (μ s)	< 1 μ s
Pulse repetition frequency (Hz)	N/A
Pulse duty cycle (%)	N/A
Pulse period resolution (μ s)	N/A
Interfaces	RS232, Ethernet, DB25 Analog/Digital, 9-pin matching bus
Additional Fieldbus Interface	None
Frontpanel	Active front panel
Harmonics (dBc)	≤ -40 dBc
Spurious content (dBc)	≤ -50 dBc
CEX operation mode	Yes
CEX input signal as required (dBm)	+ 3 dBm to + 10 dBm
CEX output signal specifications (dBm)	+ 6 dBm +/- 2 dBm
CEX connector (Ohms)	SMA
CEX Phase Shift (degrees)	-180 degrees to +180 degrees in 1 degree steps

Physical specification

Dimensions (mm x mm x mm)	441 mm (width) x 500 mm (depth) x 88 mm (height)
Weight (kg)	< 15 kg
Mounting	19" rack mounting
Clearance (mm)	80 mm to air inlet

AC power line

AC line voltage (VAC 1-phase)	Single phase 187 VAC to 265 VAC
AC line frequency (Hz)	50/60 Hz nominal
Operating AC line current (A)	3.6 A to 4.9 A
AC input power (VA)	Single phase 187 VAC to 265 VAC
Efficiency line to load (%)	> 0.69 typical
Power factor	> 0.95 typical
AC mains connection	IEC 320

Cooling

Cooling method	air cooled
----------------	------------

Protections

Reflected power limit	Yes
Overtemperature	Yes
Humidity	–
DC current limit	–
DC overload	–
RF power limit	Yes
